QEF ECLIPSE CURVED BLADE BLADE PITCHED AT 152mm TO PREVENT INGRESS OF SUNLIGHT TO A MAXIMUM ANGLE OF 62° FROM THE HORIZONTAL -Eclipse Curved Blade pitched at 152mm Bracket fixed to structural support. -Side Arms Bolted to Brackets centres to prevent ingress of sunlight to a Structure to be confirmed maximum angle of 62° from the horizontal. Depth to be confirmed Mounting Bracket details to Extruded Aluminium side arms Eclipse Curved Blade & Clip be confirmed PPC Finish PPC Finish Optional Extra Bullnose Feature Rail Optional Extra Half Round Feature Rail on Inside ALTERNATIVE INNER DETAIL ALTERNATIVE END DETAIL A Bracket -Eclipse Curved Blade Pivoting and fixing bolts through side arms & -6mm Aluminium side S/S washers / spacers Optional Extra Half Round Feature Rail END SECTION THROUGH SIDE ARM ALTERNATIVE END DETAIL B SHOWING BOLTING DETAIL

Specification

Manufacturer
Eclipseand
CurvedReference:QEFSystem, supplied and installed by QEF Ltd.Tel: +353 (0)56 776 4910Fax: +353 (0)56 776 1557.

<u>Description:</u> Extruded Aluminium Curved Blade fixed between Extruded Aluminium Side Arms.

Blade Pitch: 152mm.

Material: System manufactured from extruded aluminium alloy 6063 T6.

<u>Finish:</u> Polyester powder coated to RAL or BS colour.

<u>Dimensions:</u> As shown on drawings. Max span between support arms dependant upon loading requirements.

Performance: Direct sunlight to be eliminated through the Brise Soleil up to 62°.

Fixing: To subcontractors details. A wide range of stainless, galvanised steel or aluminium fixing brackets is available for different fixing grounds, including steel, block & curtain walling.



Commercial Centre Dublin Road Kilkenny

Tel: +353 (0)56 776 4910 Fax: +353 (0)56 776 1557 Website: www.qefitd.ie Emall: sales@qefitd.le