



QEF AC300 Acoustic Louvre Panel Format



Acoustic Performance to BS EN ISO 10140-2:2010.
SRL Test Report No: C/23553/T01

Octave Band Centre Frequency (Hz)	63	125	250	500	1k	2k	4k	8k
Transmission Loss (dB)	9.7	5.5	7.9	10.9	18.2	21.0	18.7	16.7
Acoustic Rating	Rw 17 dB							



Specification

Manufacture & Reference: QEF AC300 Acoustic Louvre System, supplied and installed by QEF Ltd.
Tel: +353 (0)56 776 4910
Email: sales@qeftd.ie

Description: Single bank pressed aluminium acoustic louvre with casement surround, panel format, fixed to structure with adjustable galvanised steel or S/S cleats.

Blade pitch: 175mm

Material: Available in aluminium, galvanised steel & colorcoat steel.

Acoustic Fill: Polyester Fibre.

Finish: Polyester powder coated to RAL or BS colour, in matt, satin or gloss finishes.

Dimensions: All Louvres are bespoke to clients needs

Performance: Acoustic performance as per table. Free area, based on 2500mm High is 27%

Fixing: All structural support by main contractor

Accessories: Bird / insect mesh, blanking / insulated blanking plate to rear. Single / Double doors.



Commercial Centre
Dublin Road
Kilkenny

Tel: +353 (0)56 776 4910
Fax: +353 (0)56 776 1557
Website: www.qeftd.ie
Email: sales@qeftd.ie

Drawn:	Date:	Scale:
RAB	21/05/2018	NTS
Dwg.No:	Rev:	
AC300 SB//PF		